



SMARTRAIL – Work Package 1

Monitoring and Inspection



Dr. Ken Gavin
Lecturer, School of Civil, Structural &
Environmental Engineering
University College Dublin



EUROPEAN
COMMISSION



Community research
Research DG
H2 Surface Transport



Objectives



WP1 aims to bring about a step change in the traditional methods of *visual inspection and ad-hoc monitoring* with integrated monitoring systems which utilize the *latest embedded sensor technology* and *optimized in-situ testing methods*.



EUROPEAN
COMMISSION



Community research
Research DG
H2 Surface Transport



Overview of Tasks

Task 1.1 Network of embedded sensor devices

Task 1.2: Instrumented Smart Slope

Task 1.3: Inspection of Slopes using NDT Techniques

Task 1.4: Development of a methodology for NDT
assessment of bridges subjected to scour

Task 1.5: Use of instrumentation to monitor the condition
of bridge structures



EUROPEAN
COMMISSION



Community research
Research DG
H2 Surface Transport



Task 1.1 Network of embedded sensor devices

**Partners Irish Rail, Slovenian Railways, EURNEX (RTU),
FERHL (VTI), ZAG and IK.**

The participants will specify *embedded sensor systems* to monitor
and control old railway networks:

for SMARTRAIL emphasis is on soil slopes and bridges



EUROPEAN
COMMISSION



Community research
Research DG
H2 Surface Transport



Task 1.2: Instrumented Smart Slope

Partners: **UCD** and Irish Rail



- An existing (disused) railway slope will be instrumented with pore pressure sensors, inclinometers, weather station etc.
- Controlled rainfall will be applied using a rainfall simulator
- Live slopes will be instrumented to provide real-time feedback



EUROPEAN
COMMISSION





Community research
Research DG
H2 Surface Transport



Survey of 150 year old railway embankments

Average slope angle = 38°






EUROPEAN
COMMISSION



Community research
Research DG
H2 Surface Transport



Slopes are Partially Saturated



- Air voids act like mini capillary tubes, drawing water up from the saturated zone below the water table by suction
- This suction provides inherent stability





EUROPEAN
COMMISSION



Community research
Research DG
H2 Surface Transport



Stability is affected by rainfall



As rain falls, suctions reduce. A wetting front develops as the ground becomes *almost* saturated from the top down



EUROPEAN
COMMISSION




Community research
Research DG
H2 Surface Transport



Effect of suction on slope stability

$$\text{FOS} = \frac{\text{Capacity}}{\text{Demand}}$$



- Stability is provided by near surface suction (-pwp)
- Rainfall causes formation of wetting front (increased pwp) reduces suction and may cause failure – typically shallow slip



EUROPEAN
COMMISSION




Community research
Research DG
H2 Surface Transport



Instrumentation: Soil Suction

UMS T4eTensiometers:

- Can measure soil pore pressure from -80kPa to 100kPa.
- External refilling.
- Accurate to .5kPa.
- Wide variety of lengths.
- Fast response.





EUROPEAN
COMMISSION




Community research
Research DG
H2 Surface Transport



Instrumentation: Soil Moisture Content

Campbell Scientific Soil moisture probes:

- The CS616 measures the volumetric water content from 0% to saturation.
- Can be buried or inserted from the surface.
- Fast response time.
- Very accurate





EUROPEAN
COMMISSION



Community research
Research DG
H2 Surface Transport



Instrumentation: Deformations

Trimble Mensei Laser Scanner

- Takes 3D laser scans.
- Accurate to 1.4mm in 50m.
- Volume change can be monitored over time by using a time sequence.





EUROPEAN
COMMISSION




Community research
Research DG
H2 Surface Transport



Task 1.3: Slope Inspection using NDT Techniques

Partners: UCD, FERHL (**NTUA**), **IGH**, Irish Rail



- (i) Method to increase data acquisition from MASW
- (ii) Develop improved models for interpreting the data e.g. GPR measurements to assess moisture content distributions in a soil mass
- (iii) Investigate fundamental relationships between geophysical measurements and soil properties, e.g. Water content and stiffness



EUROPEAN
COMMISSION



Community research
Research DG
H2 Surface Transport



Recent Slope Failures





EUROPEAN
COMMISSION



Community research
Research DG
H2 Surface Transport



Rainfall Records

Extreme Rainfall Return Periods

Location: Gorey, Co. Wexford
Average Annual Rainfall: 982

Maximum rainfall (mm) of indicated duration expected in the indicated return period.

Duration	Return Period (years)								
	1/2	1	2	5	10	20	30	50	100
1 min				1.8	2.1	2.4	2.7	3.0	3.4
2 min				3.1	3.5	4.2	4.6	5.2	5.9
5 min				5.5	6.4	7.6	8.3	9.4	10.8
10 min				7.8	9.2	11.0	12.2	13.9	16.0
15 min	4.9	6.2	6.9	9.5	11.6	14.0	15.6	17.8	21
30 min	6.7	8.3	9.3	12.6	15.4	18.5	20.5	23	27
60 min	8.8	11.0	12.3	16.4	19.7	24	26	30	34
2 hour	11.8	14.3	16.0	21.1	25	30	33	37	43
4 hour	16.2	19.6	21.5	28	32	37	41	45	52
6 hour	19.7	23.6	26	33	38	44	48	53	61
12 hour	25.4	30	33	42	49	55	60	66	75
24 hour	32	38	41	51	59	67	73	80	90
48 hour	39	46	51	63	71	81	87	95	107
96 hour									

Notes: Larger margins of error for 1, 2, 5 and 10 minute values and for 100 year return periods

M560: 16.4 M52d: 59 M560/m52d: 0.28

October

- no exceptional storms
- overall rainfall 50% above normal

November

- Rainfall 84% above normal
- Included storm on 25th with 58mm of rainfall over 6 hour




EUROPEAN
COMMISSION



Community research
Research DG
H2 Surface Transport



Cross-Section



05.12.2006




EUROPEAN
COMMISSION



Community research
Research DG
H2 Surface Transport



Geophysical Investigation



Resistivity investigation across failure plane and along track to confirm soil stratigraphy and investigate suspected lateral flow of water along embankment




EUROPEAN
COMMISSION



Community research
Research DG
H2 Surface Transport



ERT profile across track through failure plane





EUROPEAN
COMMISSION



Community research
Research DG
H2 Surface Transport





ERT Profile Along Track

NW

R2

SE

Overlap with R3






EUROPEAN
COMMISSION



Community research
Research DG
H2 Surface Transport



Seepage Analyses



Rainfall data was used to model infiltration into embankment

- FOS reduced to ≈ 1.2
- Regrading of embankment caused increase in FOS to 1.3




EUROPEAN
COMMISSION



Community research
Research DG
H2 Surface Transport



Finite Element Analysis






EUROPEAN
COMMISSION



Community research
Research DG
H2 Surface Transport



Stress distribution beneath embankment



- Geophysical investigation highlighted extent of soft organic clay present beneath the slope
- Tube samples were obtained as part of a forensic investigation
- Samples exhibited significant creep at stress levels 80 – 100 kPa



EUROPEAN
COMMISSION




Community research
Research DG
H2 Surface Transport



Task 1.4: NDT assessment of bridge foundations subjected to scour

Partners: **UCD**, NTUA, Irish Rail)



(i) Investigate geophysical techniques in field

(ii) Use of accelerometer data to measure changes in frequency response (lab – flume) and field.



EUROPEAN
COMMISSION



Community research
Research DG
H2 Surface Transport



Laboratory Investigation



Impulse Force Device

Accelerometer

Model Bridge Pier

Bed of Sand

**By varying the bed level,
we can model the scour
process on the pier**




EUROPEAN
COMMISSION



Community research
Research DG
H2 Surface Transport



Laboratory Investigation





EUROPEAN
COMMISSION





Community research
Research DG
H2 Surface Transport



Natural Frequency Analysis


Acceleration Plot



Fast Fourier
Transform



Frequency Plot





EUROPEAN
COMMISSION





Community research
Research DG
H2 Surface Transport



Damping Analysis

Acceleration Plot




Exponential
Curve Fitting



$$Y = Ae^{Bt}$$

$$B = -\xi 2\pi f \longrightarrow \xi = -\frac{B}{2\pi f}$$

Damping Plot






EUROPEAN
COMMISSION



Community research
Research DG
H2 Surface Transport



Results of Laboratory Investigation






EUROPEAN
COMMISSION



Community research
Research DG
H2 Surface Transport



Results of Laboratory Investigation





EUROPEAN
COMMISSION



Community research
Research DG
H2 Surface Transport



Present Works

- **Scale up laboratory investigation to pilot scale**
- **Instrument a free ended pier in “free field” condition**



Accelerometer(s)

Pilot Bridge Pier

**Remove sand from
base incrementally and
measure accelerations**




EUROPEAN
COMMISSION



Community research
Research DG
H2 Surface Transport



Irish Rail Bridge Instrumentation



- Hoped that train loading will adequately excite the bridge so that useful accelerometer data may be obtained
- Both the changes in frequency and damping can act as indicators of foundation stiffness change



EUROPEAN
COMMISSION



Community research
Research DG
H2 Surface Transport




Task 1.5 Use of instrumentation to monitor the condition of bridge structures

Partners: **Adaptronica** and Zag



- Instrumentation of the steel truss railways bridges with piezoelectric strain sensors with graphical interface
- A bridge weigh in motion system which is capable of separating the dynamic response will be developed
- A demonstration site in Poland underway



Questions / Comments?